

BIVITÉ

The class leading Maximus 522 is also available with a 22x5 2 deck version of the Binder + Co Bivitec screen.

problems for ordinary screening media.

Transport 19.0 m (62' 4") Working 19.90 m (65' 3")

> Transport 3.00 m (9' 10") Working 17.90 m (59' 1")

Transport 3.40 m (11' 2") Working 6.60 m (21' 7")

Tipping grid 37,200 kgs (82,026 lbs)

Top Deck 6.700 x 1.525 (22' x 5') Bottom Deck 6.100 x 1.525 (20' x 5')

> Engine CAT C4.4 engine (Tier III), 129 HP (96kW) with shutdown

radio remote control for tracks

double deck live head single shaft shredder crusher chute

The simple, patented driving mechanism of the Bivitec screen provides two vibratory movements where the polyurethane mats are expanded and compressed at high speed.

> This movement, combined with the traditional circular screening motion of Maximus screens gives a powerful screening action which prevents any potential clogging up of the screens in the harshest of operating conditions.

> > 2A Washingbay Road, Coalisland, Co Tyrone, Northern Ireland, BT714ND Office: +44 (0) 288 774 8873 Email: info@maximusscreening.com

www.maximusscreening.com





The combination of the Bivitec and Maximus names in one machine gives the

perfect screening platform for difficult, sticky applications that might cause